

**Overview**

- This Altronix power supply converts a 115VAC 60Hz input into three (3) individually regulated power limited outputs.

**Specifications**

- 5VDC, 12VDC or 24VDC simultaneous output.
- 1.75 amp @ 5VDC and 12VDC, and 1.5 amp @ 24VDC supply current.
- Class 2 Rated power limited output.
- Input 115VAC / 60Hz, 1.45 amp.
- Input fuse rated @ 3.5 amp/250V.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.
- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current .7 amp.
- Automatic switch over to stand-by battery when AC fails (zero voltage drop).
- AC fail supervision (form "C" contacts).
- Low battery supervision (form "C" contacts).
- Battery presence supervision (form "C" contacts).
- AC input and DC output LED indicators.
- Enclosure:
  - Combination knockouts are 1/2" and 3/4"
  - Accommodates up to two (2) 12VDC/12AH batteries.

**Agency Approvals**

UL 294 UL Listed for Access Control System Units.  
UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.



MEA - NYC Department of Buildings Approved.



CSFM - California State Fire Marshal Approved.

# Enclosure Dimensions

15.5"H x 12"W x 4.5"D

