

**Overview**

- These multi-agency approved multi-output power supply/chargers convert a 115VAC/60Hz input to four (4) Class 2 rated 12VDC or 24VDC power limited outputs.

AL600ULPD4

- Fuses are rated @ 3.5 amp/250V
- Grey enclosure.

AL600ULPD4R

- Red enclosure

AL600ULPD4CB

- PTCs are rated @ 2.5 amp.
- Grey enclosure.

AL600ULPD4CBR

- Red enclosure

Specifications

- 12VDC or 24VDC selectable outputs.
- 6 amp supply current.
- Class 2 Rated power limited outputs.
- Four (4) protected outputs.
- Input 115VAC / 60Hz, 1.9 amp.
- Input fuse rated @ 3.5 amp/250V.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.
- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current .7 amp.
- Automatic switch over to stand-by battery when AC fails (zero voltage drop).
- AC fail supervision (form "C" contacts).
- Low battery supervision (form "C" contacts).
- Battery presence supervision (form "C" contacts).
- AC input and DC output LED indicators.
- Enclosure:
 - Combination knockouts are 1/2" and 3/4"
 - Accommodates up to two (2) 12VDC/7AH batteries.

Agency Approvals

UL 294 UL Listed for Access Control System Units.

UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.



CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.

Enclosure Dimensions

13"H x 13.5"W x 3.25"D

