



Overview

- These multi-agency approved multi-output power supply/chargers convert a 115VAC/60Hz input to eight (8) 12VDC or 24VDC outputs.

AL600ULPD8

- Fuses are rated @ 3.5 amp/250V
- Grey enclosure.

AL600ULPD8R

- Red enclosure.

AL600ULPD8CB

- Class 2 Rated PTC protected power limited outputs rated @ 2.5 amp each.
- Grey enclosure.

AL600ULPD8CBR

- Red enclosure.

Specifications

- | | |
|---|---|
| <ul style="list-style-type: none"> • 12VDC or 24VDC selectable outputs. • 6 amp supply current. • Eight (8) protected outputs. • Input 115VAC / 60Hz, 1.9 amp. • Input fuse rated @ 3.5 amp/250V. • Filtered and electronically regulated outputs. • Short circuit and thermal overload protection. • Built-in charger for sealed lead acid or gel type batteries. • Maximum charge current .7 amp. • Automatic switch over to stand-by battery when AC fails (zero voltage drop). • AC fail supervision (form "C" contacts). • Low battery supervision (form "C" contacts). • Battery presence supervision (form "C" contacts). | <ul style="list-style-type: none"> • AC input and DC output LED indicators. • Enclosure: <ul style="list-style-type: none"> - Combination knockouts are 1/2" and 3/4" - Accommodates up to two (2) 12VDC/7AH batteries. • Product weight: <ul style="list-style-type: none"> - AL600ULPD8: 7.8 lbs. - AL600ULPD8CB: 7.9 lbs. - AL600ULPD8R: 6.2 lbs. - AL600ULPD8CBR: 6.2 lbs. • Shipping weight: <ul style="list-style-type: none"> - AL600ULPD8: 8.8 lbs. - AL600ULPD8CB: 8.8 lbs. - AL600ULPD8R: 7.2 lbs. - AL600ULPD8CBR: 7.2 lbs. |
|---|---|

Agency Approvals



UL 294 UL Listed for Access Control System Units.

UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.



CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.

Enclosure Dimensions

13.5"H x 13"W x 3.25"D

