



Overview

- These multi-agency approved single output power supply/chargers convert a 115VAC/60Hz input into one (1) 12VDC or 24VDC non-power limited output.

AL600ULX

- Grey enclosure.

AL600ULXR

- Red enclosure.

Specifications

- | | |
|--|--|
| <ul style="list-style-type: none"> • 12VDC or 24VDC selectable output. • 6 amp supply current. • Input 115VAC / 60Hz, 1.9 amp. • Input fuse rated @ 3.5 amp/250V. • Filtered and electronically regulated output. • Short circuit and thermal overload protection. • Built-in charger for sealed lead acid or gel type batteries. • Maximum charge current .7 amp. • Automatic switch over to stand-by battery when AC fails (zero voltage drop). • AC fail supervision (form “C” contacts). | <ul style="list-style-type: none"> • Low battery supervision (form “C” contacts). • Battery presence supervision (form “C” contacts). • AC input and DC output LED indicators. • Enclosure: <ul style="list-style-type: none"> - Combination knockouts are 1/2" and 3/4" - Accommodates up to two (2) 12VDC/7AH batteries. • Product weight: <ul style="list-style-type: none"> - AL600ULX: 7.6 lbs. - AL600ULXR: 6.6 lbs. • Shipping weight: <ul style="list-style-type: none"> - AL600ULX: 8.5 lbs. - AL600ULXR: 7.6 lbs. |
|--|--|

Agency Approvals



- UL 294 UL Listed for Access Control System Units.
- UL 603 UL Listed Standard for Power Supplies for Use with Burglar-Alarm Systems.
- UL 1069 UL Listed Hospital Signaling and Nurse Call Equipment.
- UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.



- CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.



- MEA - NYC Department of Buildings Approved.



- CSFM - California State Fire Marshal Approved.



- FM - Factory Mutual Approved.

Enclosure Dimensions

13.5"H x 13"W x 3.25"D

