

# eBridge1PCRM

## IP and PoE/PoE+ over Coax Receiver

### Description

Altronix eBridge1PCRM single port EoC Receiver transmits data and passes power over coax cable. eBridge1PCRM passes PoE/PoE+ up the coax to an eBridge1PCT, eBridge1PCTX or eBridge1ST transceiver. The transceiver in turn delivers that PoE compliant power to an edge device/camera. This plug and play unit facilitates system upgrades from analog to IP utilizing existing legacy Coax and eliminates the costs and labor associated with installing new network cabling. Data transmission and power over the Coax is possible up to 500m in comparison to 100m Ethernet distance (CAT5e). A maximum range from headend to the edge device/camera is 700m, taking into consideration that up to 100m of structured cable may be deployed from the receiver to the network switch and the transceiver to the edge device/camera.



eBridge1PCRM

### Key Features

- IEEE 802.3af (15W) and IEEE 802.3at (30W).
- Throughput is rated to pass 25Mbps at distances up to 500m.
- Eliminates the costs and labor associated with installing new network cabling.
- Retrofit digital IP cameras in an analog CCTV installation.
- Auto detection and protection of legacy non-PoE cameras/devices.
- Works with Megapixel, HD720, HD1080, & VGA (SD) cameras.
- Extends Network link distance in an industrial environment.
- Upgrades deployed CCTV Coax to a digital network for Retail, Casinos, Airports, Schools, Hospitals, etc.
- UL Listed in the U.S. and Canada.
- CE Approved.
- C-Tick compliant.
- Lifetime Warranty / Made in the U.S.A.

### Compatible Transceivers:



#### eBridge1PCT IP and PoE over Coax Hardened Transceiver

Delivers IP video/data over coax up to 500m @ 25Mbps.  
Supports PoE (IEEE 802.3af).  
UL/cUL Listed (UL60950-1). CE and C-Tick Approved.



#### eBridge1PCTX IP and PoE/PoE+ over Coax Hardened Transceiver

Delivers IP video/data over coax up to 500m @ 25Mbps.  
Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).  
UL/cUL Listed (UL60950-1). CE and C-Tick Approved.



#### eBridge1ST IP and PoE/PoE+ over Coax Hardened Mini Transceiver

Delivers IP video/data over coax up to 500m @ 25Mbps.  
Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).  
UL/cUL Listed (UL60950-1). CE Approved.

# eBridge1PCRM

## IP and PoE/PoE+ over Coax Receiver

### Specifications

#### Input

Voltage:  
24VDC to 56VDC Class 2 power supply (polarity observed).

#### Ethernet

Connectivity: RJ45, auto-crossover.  
Wire type: 4-pair CAT5 or better structured cable.  
Distance: up to 100m.

#### Coax

Throughput is rated to pass 25Mbps of data at distances up to 500m.  
With proper headend equipment multiple Megapixel cameras can be used.  
Speed: 10/100BaseT, half/full duplex, auto negotiation.  
Connectivity: BNC, RG-59/U or similar.

#### Indicators (LED)

Blue LED	Coax link connection.
Green LED	PoE ON.
Green LED	Power ON.
Yellow and Green LED (RJ45):	IP Link status, 10/100Base-T/active

#### Agency Listings

UL/cUL	UL 60950-1 (Information Technology Equipment).
CE	European Conformity.
C-Tick compliant.	

#### Physical and Environmental

<b>Dimensions (H x W x D)</b>	
3.5" x 4.375" x 1" (88.9mm x 111.1mm x 25.4mm).	
<b>Weight (approx.)</b>	
Product Weight	0.275 lbs. (0.125 kg).
Shipping Weight	0.6 lbs. (0.27 kg).
<b>Temperature</b>	
Operating	-20°C to 49°C (-4°F to 120.2°F).
Storage	-20°C to 70°C (-4° to 158°F).
Relative Humidity	85% +/-5%.
Operating Altitude:	-304.8 to 2,000m.
BTU/Hr. (approx.):	24VDC: 18 BTU/Hr. 56VDC: 26 BTU/Hr.

### Accessories



#### NetWay1D

Single port Hi-PoE midspan injector for standard and enhanced power network infrastructure. Provides Class 2 power-limited output rated @ 56VDC/60W. Operates at 115VAC or 230VAC input. UL/cUL Listed (UL60950-1). CE Approved.