

## ECT-D32V2

### 2 MP Outdoor EXIR VF Dome Camera

## TurboHD™



- 2 MP High Performance CMOS
- Up to 1920 x 1080 Resolution
- 2.8 mm to 12 mm Manual Varifocal Lens
- EXIR 2.0 up to 130 ft (40 m) IR Range
- Smart IR
- DWDR, BLC
- Multiprotocol Output: TVI/AHD/CVI/CVBS
- IP66, IK10 Protection

The Hikvision ECT-D32V2 Outdoor EXIR VF Dome Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 130 feet (40 meters).

The 2.8 mm to 12 mm manual varifocal lens is optimized for viewing angles that fit any situation.







**Available models:**  
ECT- D32V2



# Specifications

ECT- D32V2	
<b>Camera</b>	
Image Sensor	2 MP CMOS image sensor
Signal System	NTSC
Effective Pixels	1920 (H) x 1080 (V)
Minimum Illumination	0.01 Lux @ (f/1.2, AGC on), 0 Lux with IR
Shutter Speed	1/25 (1/30) s to 1/50,000 s
Lens	2.8 mm to 12 mm manual varifocal lens
Horizontal Field of View	111.5° to 33.4°
Lens Mount	Ø14
Day / Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 30 fps
<b>Menu</b>	
AGC	High/medium/low/off
D/N Mode	Auto/color/BW (black and white)
BLC	Supported
DWDR	Supported
Language	English
Functions	Brightness, sharpness, DNR, mirror, smart IR
<b>Interface</b>	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
<b>General</b>	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%
Power Consumption	Maximum 3.9 W
Protection Level	IP66, IK10
Material	Metal
IR Range	Up to 130 ft (40 m)
Dimensions	Ø5.11" x 5.62" (Ø130 mm x 143 mm)
Weight	Approximately 1.39 lbs (630 g)

# Accessories

					
<b>PC140*</b> Pendant Cap	<b>DM45 Adapter Plate</b> Included with Camera	<b>CB140-DM45</b> Conduit Base	<b>PM</b> Pole Mount	<b>CM</b> Corner Mount	<b>SRSL</b> Sun Rain Shield Large

\*Requires DM45 Adapter Plate

# Dimensions

