



HD-TVI 2MP Intensifier® Dome Camera

HT7250T

5-50mm varifocal lens, dark gray housing



Features

- Full HD resolution over coax
- Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Superior low-light performance
- Amplify existing light with no distance limitation
- With presets for different scenarios
- Signal distance up to 1600 ft. (depending on coax quality)*
- Full OSD operation through on-board control and UTC (up the coax)
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- Chameleon Cover™: snaps on and can be painted to match any décor!¹
- 3 axis lens mount
- 12VDC & 24VAC dual voltage operation
- Vandal / tamper resistant
- IP67 compliant, weather resistant
- UL listed
- 5 year warranty



Shown with included paintable, snap-on Chameleon Cover™



Camera Specifications

Image Sensor	1/3" Sony Exmor CMOS, 2MP
Effective Pixels	1985 (H) x 1105 (V)
Total Pixels	2001 (H) x 1121 (V)
Resolution	1920x1080 @30fps / 1280x720 @ 60fps
Minimum Illumination	0.001 lux (sense-up x32)
Scanning System	Progressive
Video Output	1.0Vp-p / 75 Ohms
S/N Ratio	More than 50dB
AGC	0-20 level adjustable
Electronic Shutter	Auto / Manual (1/25, 1/30 – 1/30,000 sec.) / Flicker
Brightness	0-20 level adjustable
Sense-up	2x – 32x (adjustable)
WDR	On (Low / Middle / High) / Off
Day/Night	Auto / Color / BW / EXT
Motion Detection	On / Off (4 zones)
Privacy Masking	On / Off (16 zone)

White Balance	Auto / AWB / AWC-Set / Manual
Digital Noise Reduction	Off / Low / Middle / High
Mirror	On / Off
V-Flip	On / Off
Sharpness	0-20 level adjustable
Lens Shading	On / Off
Test Monitor Output	CVBS
Communication	UTC (up the coax)

Operating & Unit Specifications

Power Supply	12VDC / 24VAC dual voltage (power supply not included)
Power Consumption	12VDC, 500mA max. / 24VAC, 195mA max.
Operating Temperature	-4°F - 140°F
Operating Humidity	20% - 95% RH
Unit Dimensions	3.46" (H) x 5.10" (Dia.)
Unit Weight	1 lbs.
Certifications	FCC, RoHS

Optional Accessories



(use with INTWM only)

¹Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended. ²To preserve signal quality and distance, Speco Technologies recommends using coax with a 100% copper center conductor and at least 95% braided copper shield. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/2/17