

JUMBO PUSH PLATES

REQUEST TO EXIT STATIONS



Model JP1



Model JP2



Model JP3

Switch Type	JP1 Models	JP2 Models	JP3 Models
SPDT	JP1-1	JP2-1	JP3-1
DPDT	JP1-2	JP2-2	JP3-2
Pneumatic Time Delay 2 to 60 Seconds	JP1-5	JP2-5	JP3-5

- Heavy duty 5.5 inch square steel push plate
- Mounts on standard two gang electrical box

Non-pneumatic Model Specifications -

- Momentary action switch
- Contact rating: 4A @ 28VDC
- Temperature range -20°F to +150°F
- Depth behind plate is 1.5 inches

Pneumatic Model Specifications -

- Time delay operator does not require power for timing function.
- One Normally-Open contact pair and one Normally-Closed contact pair
- Contacts rated 10A @ 35VDC
- Time range settable between 2 and 60 seconds
- Switch time is repeatable ±10%
- Temperature range +15°F to +120°F
- Switch depth 2.25" behind plate



ASSA ABLOY

Alarm Controls
 19 Brandywine Drive
 Deer Park, New York 11729
 (800) 645-5538
 www.alarmcontrols.com

ASSA ABLOY, the global leader
 in door opening solutions