

4-Port Gigabit Ethernet Switch, 2 Combo (SFP/RJ45) Uplinks, Hardened (-40 to 75°C)



Features

- 4 ports Hardened Gigabit with 2 port Combo SFP/RJ45
- 2 Gigabit combo SFP/RJ45 Uplink Ports
- -40° F to 185° F Operating Temperature
- Auto-Sensing ports (MDI/MDIX)
- Supports Store & Forward Operation
- 8k MAC Table/ 1M Package data cache
- Fanless- heat dissipation design
- Redundant Power design
- Support 4KV Lighting Protection/ Level3 ESD



Specifications	KA-GH6
Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE802.3z 1000BASE-X
Backplane	14 Gbps
Features	4 10/100/1000M RJ-45 ports 2 Gigabit combo SFP/RJ45 Uplink Ports
Data Transfer Rate	Ethernet: 10Mbps/Half-Duplex 20Mbps/Full-Duplex Fast Ethernet: 100Mbps/Half-Duplex 200Mbps/Full-Duplex Gigabit Ethernet: 2000Mbps/Full-Duplex
Transmission Media	1000BaseX SX/LX Fiber 10BaseT/100BaseTX Cat. 5 UTP/STP, 1000BaseT Cat. 5, 6 UTP
LED Indicators	Per Port: Per Unit: Link/Act, Fiber Power
Filtering/Forwarding Rate	1000Mbps / 1,488,000pps 100Mbps / 148,800pps 10Mbps / 14,880pps
Dimensions	6.42 x 4.33 x 1.81 inches (W x D x H)
Weight	Unit: 11bs 12oz Shipping:
Temp	-40 to 167 F -40 to 158 F Operating Storage
Humidity	0% to 95% RH (non-condensing)
Certifications	FCC, CE

Sales and Support: (385) 999-8887
Sales@syncomtechnologies.com
Please send Orders to:
Orders@syncomtechnologies.com
www.syncomtechnologies.com



Package Contents

- KA-GH6
- Power Cord
- Wall/Din mount
- Quick Guide