

Emergency Panic Stations



Model KR-1
Latching Push Button
With Key Reset



Model PBM-1-4
Momentary Push Button
Mounted on a Red Plate



Model PBL-1-L2
Latching Push Button
With Illuminated Button

- Single Gang 430 Stainless Steel Wallplate
- Normally-Open and/or Normally-Closed Contact Pairs
- Contacts Rated 10A @ 35 VDC or 120VAC
- Temperature Range -25°C to +70°C
- Switch Connection via Screw Terminals
- Switch Depth 2" Behind Plate, 2.5" for Illuminated Models
- UL Listed Components
- Weather-Proof to IP65 Standard, KR models to IP40 Standard
- Large 1.5" Diameter Red Mushroom Button
- Custom Plate Marking Available

MODEL	CONTACTS	PLATE	ILLUMINATION <small>(not available on KR Models)</small>	GUARD RING
<u>PBM</u> MOMENTARY OPERATOR <u>PBL</u> LATCHING OPERATOR <u>KR</u> LATCHING OPERATOR KEY RESET	<u>1</u> 1 N/O PAIR and 1 N/C PAIR <u>2</u> 2 N/O PAIRS <u>3</u> 2 N/C PAIRS <u>4</u> 1 N/C PAIR <u>5</u> 1 N/O PAIR	<u>1</u> 302 STAINLESS <u>2</u> WHITE <u>3</u> IVORY <u>4</u> RED <u>5</u> 1.75" STAINLESS <u>6</u> 1.75" RED	<u>L1</u> 6 VDC <u>L2</u> 12 VDC <u>L3</u> 24 VDC <u>L4</u> 120 VAC	<u>GR</u>
<div style="display: flex; justify-content: space-around; margin-top: 10px;"> PBL- 1- 4- L2- GR </div>				

Part Number Example -
Latching push button with one N/O and one N/C contact pair on a red plate, 12VDC illumination and guard ring.



Alarm Controls
19 Brandywine Drive
Deer Park, New York 11729
(800) 645-5538
www.alarmscontrols.com

ASSA ABLOY, the global leader
in door opening solutions