



LI381 Corridor Light LI382 Corridor Zone Light Specification Sheet

IL518
Section E
Rev. 17 - 08/2010



**LI381 Corridor Light
LI382 Corridor Zone Light**

ARCHITECTS' AND ENGINEERS' SPECIFICATION

Corridor lights shall be TekTone® LI381 Corridor Light and LI382 Corridor Zone Light, or approved equal. Lights shall include a white flame-retardant translucent polystyrene plastic lens mounted on a flame-retardant (UL® 94V-0) plastic panel. The lens shall be removable without the use of tools for ease of bulb replacement. The LI382 shall provide for two bulbs, one white bulb and one red covered bulb, to differentiate between normal and emergency calls

The LI381 and LI382 shall be UL® 1069 Listed.

FEATURES

The LI381 Corridor Light and LI382 Corridor Zone Light provide visual indication of calls when used with a nurse call system, emergency call system, or similar application. Emergency calls are indicated by the rapid flashing of the LI381 Corridor Light associated with the calling station. Normal calls produce a steady illumination.

The LI382 Corridor Zone Light indicates an emergency call by the rapid flashing of the red-covered bulb associated with the zone or area from which an emergency call has been placed. Normal calls are indicated by a steady illumination of the white bulb. If an emergency and normal call are placed in the same zone at the same time, the red covered bulb connected to the emergency station will flash rapidly, while the white bulb associated with the normal call will maintain a steady illumination.

The standard mounting plate accommodates both models and features an easily removable white flame-retardant translucent polystyrene plastic lens for bulb replacement.

- UL® 1069 Listed
- Snap-in lens
- Easy bulb replacement
- Attractive flame-retardant HIPS30 plastic panel
- Excellent visibility

SPECIFICATIONS

Dimensions:	Height:	4.5625" (115 mm)
	Width:	4.5625" (115 mm)
	Depth:	3.3" (84 mm)
Bulbs:	#1829 28V 70 mA	
Power:	LI381:	24 VDC, 51mA
	LI382:	24 VDC, 102mA
Finish:	White flame-retardant translucent polystyrene plastic lens mounted on a flame-retardant (UL® 94V-0) plastic panel.	
Housing:	Fits either standard dual gang box and ring or single gang box and ring.	

REQUIRED COMPONENTS

Tek-CARE® NC110,
NC150, NC200 or NC300II Nurse Call Systems
CM800 Emergency Call System

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net
Phone: (828) 524-9967 • Fax: (828) 524-9968 • Tech Support: Choose option 2 • Sales: Choose option 3
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)