

# VANDAL RESISTANT DOUBLE GANG PUSH PLATES

## FOR ACCESS CONTROL APPLICATIONS



PRESS TO OPERATE DOOR  
CLEAR FINISH  
BLACK FILL



ADA PUSH TO OPEN  
BLUE FINISH  
WHITE FILL



PUSH TO EXIT  
BRONZE FINISH  
BLACK FILL

- Machined from solid aluminum with engraved text and anodized finish
- Tamper resistant mounting
- Designed for use in high traffic areas
- Mounts on a standard double gang electrical box

SWITCH TYPE	FINISH	ENGRAVING	FILL
<u>1</u> SPDT MOMENTARY ACTION	<u>1</u> CLEAR	<u>1</u> PUSH TO EXIT	<u>1</u> BLACK
<u>2</u> DPDT MOMENTARY ACTION	<u>2</u> BRONZE	<u>2</u> PUSH TO OPERATE DOOR	<u>2</u> RED
<u>5</u> PNEUMATIC TIME DELAY (2 TO 60 SECONDS)	<u>3</u> BRASS	<u>3</u> ADA SYMBOL PUSH TO OPEN	<u>3</u> WHITE
	<u>4</u> BLUE		<u>4</u> BLUE
	<u>5</u> BLACK		

PD	1-	1	1	1
----	----	---	---	---

Part Number Example -

For a Double Gang Plate with a SPDT Momentary Action Switch, Clear Finish, Engraved "PUSH TO EXIT" and filled in Black Ink.

SPDT and DPDT Switch Specifications -  
 Contact Rating ..... 4A @ 28VDC  
 Depth Behind Plate..... 1.375"  
 Switches terminated in 22AWG colored leads -  
 Common..... White  
 Normally Closed ..... Red  
 Normally Open..... Blue

Pneumatic Switch Specifications -  
 Contact Rating ..... 2A @ 28VDC  
 Depth Behind Plate..... 2.25"  
 Switches terminated in 22AWG colored leads -  
 Normally Closed Pair.. Red  
 Normally Open Pair .... Blue



**ASSA ABLOY**

**Alarm Controls**  
 19 Brandywine Drive  
 Deer Park, New York 11729  
 (800) 645-5538  
[www.alarmcontrols.com](http://www.alarmcontrols.com)

**ASSA ABLOY, the global leader**  
 in door opening solutions