

# VANDAL RESISTANT PUSH PLATES

## FOR ACCESS CONTROL APPLICATIONS



**NARROW PLATE**  
BRONZE FINISH  
WHITE FILL



**NARROW PLATE**  
BLUE FINISH  
WHITE FILL



**T-STYLE PLATE**  
CLEAR FINISH  
RED FILL



**SINGLE GANG PLATE**  
CLEAR FINISH  
BLACK FILL

- Machined from solid aluminum with engraved text and anodized finish
- Tamper resistant mounting
- Designed for use in high traffic areas
- Narrow Plate is just 1.875" wide and is suitable for mullion mounting
- T-Style and Single Gang Plates mount on a standard single gang electrical box

PLATE	SWITCH TYPE	FINISH	ENGRAVING	FILL
<b>PN</b> NARROW	<u>1</u> SPDT MOMENTARY ACTION	<u>1</u> CLEAR	<u>1</u> PUSH TO EXIT	<u>1</u> BLACK
<b>PT</b> T-STYLE	<u>2</u> DPDT MOMENTARY ACTION	<u>2</u> BRONZE	<u>2</u> PUSH TO OPERATE	<u>2</u> RED
<b>PS</b> SINGLE GANG	<u>5</u> PNEUMATIC TIME DELAY (2 TO 60 SECONDS)	<u>3</u> BRASS	<u>3</u> PUSH TO OPEN	<u>3</u> WHITE
		<u>4</u> BLUE	<u>4</u> ADA SYMBOL PUSH TO OPEN	<u>4</u> BLUE
		<u>5</u> BLACK	<u>5</u> EMERGENCY DOOR RELEASE	

<b>PS</b>	<b>1-</b>	<b>1</b>	<b>1</b>	<b>1</b>
-----------	-----------	----------	----------	----------

Part Number Example -

For a Single Gang Plate with a SPDT Momentary Action Switch, Clear Finish, Engraved "PUSH TO EXIT" and filled in Black Ink.

SPDT and DPDT Switch Specifications -  
 Contact Rating ..... 4A @ 28VDC  
 Depth Behind Plate..... 1.375"  
 Switches terminated in 22AWG colored leads -  
 Common..... White  
 Normally Closed ..... Red  
 Normally Open..... Blue

Pneumatic Switch Specifications -  
 Contact Rating ..... 2A @ 28VDC  
 Depth Behind Plate..... 2.25"  
 Switches terminated in 22AWG colored leads -  
 Normally Closed Pair.. Red  
 Normally Open Pair .... Blue



**ASSA ABLOY**

**Alarm Controls**  
 19 Brandywine Drive  
 Deer Park, New York 11729  
 (800) 645-5538  
 www.alarmcontrols.com

**ASSA ABLOY, the global leader**  
 in door opening solutions