

PT2724

Two Channel Annual Event Timer

Description

Altronix PT2724 extremely versatile two channel 365 Day 24 Hour Timer/Controller is designed to support a wide range of applications. Such applications include: Home and Building Automation, Security, Access Control, Lighting Control, etc. PT2724 is equipped with two independently controlled form "C" relay contact that provides many latching and/or momentary operations during a program schedule of your choice. The EE-Prom memory allows for programming of unit prior to/or during field installation. Events may be set for single or multiple operations on a daily and/or weekly schedule. The block programming feature enables repeating an event on any combination of consecutive days. PT2724 will compensate for daylight savings time if desired. It automatically adjusts for leap year and individually selected holiday exceptions and can be programmed to override regularly scheduled events.



PT2724

Specifications

Input

Voltage 12 or 24VAC or VDC operation.

Relay

Contact Rating Form "C" 10A/120VAC or 28VDC contacts.

Standby Current 10mA (relay off)
50mA (relay on).

Tandem relay mode allows both channels to activate simultaneously for all events.

Timer

EE-Prom memory protects against loss of programming due to power failure.

Accurate crystal controlled clock.

Momentary and/or Latching Events.

50 individually programmed daily/weekly events.

Block programming capacity can accommodate a total of 350 events per week.

10 programmable Holiday dates.

"First man in" option.

Standard or Daylight Savings Time settings.

Automatic compensation for leap year.

Indicators (LCD)

Alphanumeric LCD display simplifies programming.

Back-up Battery *(not included)*

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

Optional lithium battery (Altronix LB2032) backup maintains clock.

Physical and Environmental

Dimensions (L x W x H)

5.25" x 3.6" x 1" (133.4mm x 91.4mm x 25.4mm).

Product Weight 0.48 lbs. (0.22 kg).

Shipping Weight 0.5 lbs. (0.23 kg).

Temperature

Operating -20°C to 49°C (-4°F to 120°F).

Storage -25°C to 70°C (-13°F to 158°F).

Relative Humidity 85% +/-5%.

PT2724

Two Channel Annual Event Timer

Board Dimensions (L x W x H) and Drawing

5.25" x 3.6" x 1" (133.4mm x 91.4mm x 25.4mm)

