

## R2416UL Series AC CCTV Rack Power Supplies

### Description

Altronix R2416UL Series Rack Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via sixteen (16) fuse or PTC protected outputs for powering CCTV cameras, heaters, and other video accessories.



R2416UL

### Key Features

- Sixteen (16) fuse or PTC protected outputs.
- 24VAC or 28VAC outputs.
- Surge protection.
- Individual power LED indicators.
- Illuminated power disconnect circuit breaker with manual reset.
- Removable terminal blocks with locking screw flanges.
- Spare fuses provided (all models with primary and/or secondary fuses).
- UL Listed in the U.S. and Canada.
- CE Approved.
- Lifetime Warranty / Made in the U.S.A.

### R2416UL Series Power Supply Configuration Reference Chart

Altronix Model Number	Output Voltage (VAC)	Total Output Current (Power)	Number of Outputs	PTC Protected Power-Limited Outputs (auto-resettable)	Fuse Protected Outputs	Output Current (max per output)	Main Fuse Ratings	115VAC 50/60Hz Input Current		
R2416UL	24VAC	7A	16	-	✓	3.5A	3.5A/ 250V	2.9A		
	28VAC	6A								
R2416ULCB	24VAC	7A		✓	-	2.5A				
	28VAC	6A								
R2416300UL	24VAC	12.5A		-	✓	3.5A	-	3A		
	28VAC	10A								
R2416300ULCB	24VAC	12.5A		✓	-	2.5A				
	28VAC	10A								
R2416600UL*	24VAC	25A		-	✓	3.5A				6A
	28VAC	20A								
R2416600ULCB	24VAC	25A		✓	-	2.5A				
	28VAC	20A								

\*24VAC models: Outputs 1-8 provide 12.5A (300VA) max. Outputs 9-16 provide 12.5A (300VA) max.

\*28VAC models: Outputs 1-8 provide 10A (280VA) max. Outputs 9-16 provide 10A (280VA) max.

# R2416UL Series

## AC CCTV Rack Power Supplies



### Specifications

#### Input

Voltage 115VAC, 50/60Hz.  
 Fusing See Reference Chart.

#### Outputs

Voltage 24VAC or 28VAC  
 Current Varies, see Reference Chart  
 Protection Fused 3.5A / PTC 2.5A

#### Indicators (LED)

Output Sixteen (16) individual LEDs.

#### Agency Listings

Commercial CCTV Equipment UL2044  
 Audio, Video and Similar Equipment CSA Standard C22.2 No.1-98  
 CE European Conformity

#### Physical and Environmental

2U rack mount chassis for use in standard EIA 19" rack.

#### Dimensions (H x W x D):

3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm).

#### Weight:

Model	Product Weight	Shipping Weight
R2416UL(CB)	16.15 lbs. (7.33 kg)	17.15 lbs. (7.78 kg)
R2416300UL(CB)	17.2 lbs. (7.80 kg)	18.2 lbs. (8.26 kg)
R2416600UL(CB)	23.0 lbs. (10.43 kg)	24.0 lbs. (10.89 kg)

#### Temperature:

Operating 0°C to 49°C (32°F to 120°F).  
 Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

#### BTU/Hr. (approx.):

Model	24VAC	28VAC
R2416UL(CB)	90	90
R2416300UL(CB)	156	143
R2416600UL(CB)	307	287