

## ReServ2WP Video Surveillance UPS

### Description

Altronix ReServ2WP Outdoor Video Surveillance UPS is designed to provide power for 24VAC cameras during normal or power outage conditions. True sine wave regulated AC outputs.



### Specifications

#### Input

Voltage 115VAC, 60Hz, 3.5A.

#### Outputs

16 individual PTC protected power-limited auto-resettable outputs rated 1A each.

Voltage 24VAC.

Current 4A (0.25A per device, 1A max.)  
(Ambient Temperature -33°C to 30°C).  
3.5A (0.21A per device, 1A max.)  
(Ambient Temperature -33° to 42° C).

Other Short circuit and thermal overload protection.

#### Back-up Battery *(not included)*

Type Sealed lead acid or gel type.  
Failover Upon AC loss, instantaneous.

#### Supervision

AC Failure Form "C" contacts.  
Low Battery Form "C" contacts.

#### Indicators (Audio and LED)

Input Input voltage is present.  
DC Output Powered.  
Outputs Individual Indicators.  
Audio AC Fail and Battery Fail.

#### Agency Listings

UL/cUL UL60950-1 (Information Technology).  
CE European Conformity.

#### Physical and Environmental

##### Dimensions (H x W x D)

17.375" x 12" x 6.5" (441.3mm x 304.8mm x 165.1mm).  
Enclosure accommodates up to two (2) 12VDC/127AH batteries.  
NEMA4 / IP66 Rated Enclosure.

Product Weight 21.5 lbs. (9.7 kg).

Shipping Weight 23.0 lbs. (10.43 kg).

##### Temperature

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 49 BTU/Hr.

### Accessories

PMK1 Pole Mount Kit (order separately)

PMK1 pole mount kit is designed to simplify installation of outdoor units.

It accommodates 2" - 8" (diameter) poles.

Kit includes:

- Two (2) powder coated steel mount brackets.
- Four (4) stainless steel bolts.
- Four (4) stainless steel lock washers.
- Two (2) wormgear quick release straps.

