

# ReServ4WP

## Video Surveillance UPS

### Description

Altronix ReServ4WP Outdoor Video Surveillance UPS is designed to simultaneously provide power for 24VAC and 12VDC cameras during normal or power outage conditions. True sine wave regulated AC outputs and regulated DC outputs.



ReServ4WP

### Specifications

#### Input

Voltage 115VAC, 60Hz, 3.5A.

#### Outputs

4 individual auto-resettable PTC protected outputs:

Voltage Two (2) outputs @ 24VAC. PTCs rated @ 4A.  
Two (2) outputs @ 12VDC. PTCs rated @ 1A.

Current 24VAC @ 4A.  
(Ambient Temperature -33°C to 42°C).

Other Short circuit and thermal overload protection.

#### Back-up Battery *(not included)*

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

#### Supervision

AC Failure Form "C" contacts.

Low Battery Form "C" contacts.

#### Indicators (Audio and LED)

Input Input voltage is present.

DC Output Powered.

Outputs Individual Indicators.

Audio AC Fail and Battery Fail.

#### Agency Listings

CE European Conformity.

#### Physical and Environmental

##### Dimensions (H x W x D)

17.375" x 12" x 6.5" (441.3mm x 304.8mm x 165.1mm).

Enclosure accommodates up to two (2) 12VDC/127AH batteries.

NEMA4 / IP66 Rated Enclosure.

Product Weight 21.5 lbs. (9.7 kg).

Shipping Weight 23.0 lbs. (10.43 kg).

##### Temperature

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 37 BTU/Hr.

### Accessories

PMK1 Pole Mount Kit (order separately)

PMK1 pole mount kit is designed to simplify installation of outdoor units.

It accommodates 2" - 8"(diameter) poles.

Kit includes:

- Two (2) powder coated steel mount brackets.
- Four (4) stainless steel bolts.
- Four (4) stainless steel lock washers.
- Two (2) wormgear quick release straps.



PMK1