



Models TS-6, TS-7, TS-8, TS-9

Push Buttons

Specifications

- Momentary action switch
- DPDT contacts rated 3A at 35 VDC or 120 VAC
- Operates on 12 or 24 VAC or VDC
- Switch depth behind plate: 1-1/4"
- Operating temperature: -13 to +158F [-25 to +70C]
- UL listed and CSA certified components

Features

- 5/8" x 7/8" green rectangular push button, available in single gang and narrow wall plate
- Switch illuminated with hi-brightness LED
- Labeled "PUSH TO EXIT"
- Switch terminated with color leads

Options

- 430 satin stainless steel wall plate
- Narrow 1-3/4" 302 stainless satin steel wall plate
- Red & green LEDs operate on 12 or 24 VDC, independently wired
- Other wall plate finishes available
- Other switch cap finishes available
- Custom legends can be provided
- Order TS-6 and TS-7 for Single Gang wall plate
- Order TS-8 and TS-9 for Narrow wall plate

Certifications & Listings

- UL 294 listed

Models

TS-6

UL 5/8" x 7/8" Green Illuminated Push Button, DPDT 3A Continuous Contacts, Red & Green LEDs, "PUSH TO EXIT", Single Gang

TS-7

UL 5/8" x 7/8" Green Illuminated Push Button, DPDT 3A Continuous Contacts, "PUSH TO EXIT" Single Gang, Stainless Steel Plate

TS-8

UL 5/8" x 7/8" Green Illuminated Push Button, DPDT 3A Continuous Contacts, Red & Green LEDs, "PUSH TO EXIT", 1-3/4" Stainless Steel Plate

TS-9

UL 5/8" x 7/8" Green Illuminated Push Button, DPDT 3A Continuous Contacts, "PUSH TO EXIT", 1-3/4" Stainless Steel Plate

ALARM CONTROLS



ASSA ABLOY