MODEL TS-9



- GREEN .650 x .875 INCH PUSHBUTTON
- LABELED "PUSH TO EXIT"
- MOMENTARY ACTION SWITCH
- D.P.D.T. CONTACTS RATED 2A.@12 28 VDC
- SWITCH TERMINATED WITH 10" LEADS
- SWITCH ILLUMINATED WITH HI BRIGHTNESS LED
- SWITCH MOUNTED ON NARROW 1.75" 302 STAINLESS STEEL WALLPLATE
- SWITCH DEPTH 1.25" BEHIND PLATE
- CONFORMS TO U.L. STANDARD 294 FOR ACCESS CONTROL, U.L. FILE NUMBER SA32686



ALARM CONTROLS CORPORATION 19 BRANDYWINE DRIVE DEER PARK, NY 11729

1 631 586-4220 1 800 645-5538 WWW.ALARMCONTROLS.COM EMAIL INFO@ALARMCONTROLS.COM

INSTALLATION INSTRUCTIONS MODELS TS-6, TS-7, TS-8, TS-9



LEDS AVAILABLE ONLY ON TS-6 AND TS-8 **REAR VIEW OF PLATE** LED CURRENT RATING 7 MA. @ 12 VDC, 15 MA. @ 24 VDC **BLACK LEAD NEGATIVE GREEN LED RED LEAD POSITIVE BLACK LEAD NEGATIVE** RED LED **RED LEAD POSITIVE** ➤ YELLOW LEAD (+) POSITIVE SWITCH LED 9 MA. @ 12 OR 24 VOLTS DC BLACK LEAD (-) NEGATIVE ► RED LEAD N/C CONTACT ► BLUE LEAD N/O CONTACT **SWITCH 1** Г WHITE LEAD COM CONTACT SWITCH CONTACTS RATED 2 A. @ 12 - 28 VDC WHITE LEAD COM CONTACT BLUE LEAD N/O CONTACT SWITCH 2 RED LEAD N/C CONTACT

> MOUNT WALLPLATE IN A VERTICAL POSITION MODELS TS-6, TS-7, TS-8 & TS-9

MODELS TS-6, TS-7, TS-8 & TS-9 SHOULD BE MOUNTED IN A 2.5 INCH DEEP ELECTRICAL BOX FOR 24 VOLT SWITCH LED OPERATION ADD 1000 OHM 1/2 WATT RESISTOR IN SERIES WITH YELLOW LEAD. INSULATE RESISTOR TO PREVENT SHORTING.

ALARM CONTROLS CORPORATION 19 BRANDYWINE DRIVE P.O. BOX 280 DEER PARK, NY 11729

PH: 1 800 645-5538 1 631 586-4220 FAX ; 1 631 586-6500 WWW.ALARMCONTROLS.COM EMAIL: INFO@ALARMCONTROLS.COM