

## VertiLine16Di CCTV Isolated Rack Mount Power Supply



VertiLine16Di

### Description

Altronix Vertiline16Di CCTV Isolated Rack Mount Power Supply provides sixteen (16) Class 2 rated PTC protected power-limited auto-resettable outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression.

### Specifications

#### Input

**Voltage** 115VAC, 60Hz, 7A or  
230VAC, 50/60Hz, 4A.

#### Output

Sixteen (16) electronically isoated individually selectable power outputs with OFF position.

**Voltage** 24VAC or 28VAC.

**Current** 16A max. total supply current.

**Fusing** Individual outputs' PTCs rated @ 2.5A.

**Other** Short circuit and thermal overload protection.  
Filtered and regulated.

#### Indicators (LED)

**Master** Illuminated master power disconnect  
circuit breaker with manual reset.

**Output** Sixteen (16) individual LEDs.

#### Agency Listings

**UL** UL2044 (Commercial CCTV Equipment).

**cUL** CSA Standard C22.2 No.1-04,  
Audio, Video and Similar Equipment.

**CE** European Conformity.

**C-Tick** compliant.

#### Physical and Environmental

##### Dimensions (H x W x D)

1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).

**Product Weight** 12.15 lbs. (5.51 kg).

**Shipping Weight** 13.45 lbs. (6.1 kg).

##### Temperature

**Operating** 0°C to 49°C (32°F to 120°F).

**Storage** -20°C to 70°C (-4°F to 158°F).

**Relative Humidity** 85% +/-5%.

##### BTU/Hr. (approx.):

24VAC: 197 BTU/Hr.

28VAC: 229 BTU/Hr.