



## VertiLine83C -

## **CCTV Rack Mount Power Supply**

## Description

Altronix Vertiline83C CCTV Rack Mount Power Supply provides eight (8) fuse protected power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/ or 28VAC power outputs with surge suppression.



## Specifications -

Input

Voltage 115VAC, 60Hz, 3A.

Output

Eight (8) individually selectable power outputs with OFF position.

Voltage 24VAC or 28VAC.

Current 5A max. total supply currect.

Fusing Individual outputs' fuses rated @ 3A.

Main fuse rated @ 10A.

Other Short circuit and thermal overload protection.

Filtered and regulated.

Indicators (LED)

Master Illuminated master power disconnect

circuit breaker with manual reset.

Output Eight (8) individual LEDs.

**Agency Listings** 

UL UL2044 (Commercial CCTV Equipment).

cUL CSA Standard C22.2 No.1-04,

Audio, Video and Similar Equipment.

CE European Conformity.

Physical and Environmental

Dimensions (H x W x D)

1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).

Product Weight 9.3 lbs. (2.97 kg). Shipping Weight 7.85 lbs. (3.56 kg).

Temperature

Operating 0°C to 49°C (32°F to 120°F). Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 24VAC: 123 BTU/Hr. 28VAC: 143 BTU/Hr.