

# 19RTV

## CCTV Monitor Value Line



- **World Leading Active Matrix TFT-LCD Panel**  
Truly flat LCD screen delivers razor sharp images
- **Hi Performance Image Proceseeing Circuit**  
3D Comb filter and Deinterlace function realize perfect images
- **Real Industrial Mechanical Design**  
Rigid case comes with Heavy duty mold vessel, LCD protection glass
- **Versatile terminals for Security and Industrial Solution**  
Multiple input and output of Video(BNC Type), Audio, S-Video and RGB
- **Unique Stand**  
Allows for easy cable management, wall mounting

### SPECS

|                                   |  |   |                  |
|-----------------------------------|--|---|------------------|
| <b>Display</b>                    | Screen Size                                    | 19"   |                  |
|                                   | Resolution                                     | 1280 x 1024@60Hz  |                  |
|                                   | Contrast Ratio                                 | 800:1   |                  |
|                                   | Brightness                                     | 300cd/m2  |                  |
|                                   | Aspect Ratio                                   | 5:4   |                  |
|                                   | Color Depth                                    | 16.2M   |                  |
|                                   | Viewing Angle (H / V)                          | 160°/160°   |                  |
|                                   | Pixel Pitch                                    | 0.294mm   |                  |
|                                   | Response Time                                  | 5ms   |                  |
|                                   | Scanning Frequency (H / V)                     | 31~64KHz / 56~75Hz  |                  |
|                                   | Video System                                   | NTSC / PAL  |                  |
| <b>Interface</b>                  | RGB In (15-pin)                                | 1   |                  |
|                                   | Video In / Out (BNC Jack)                      | 2 / 2   |                  |
|                                   | Audio In / Out                                 | 2 (LEFT/ Right) / Not Available                                     |                  |
|                                   | S-Video In / Out                               | 1 / 1   |                  |
|                                   | Component In                                   | Not Available   |                  |
|                                   | DVI In   | Not Available   |                  |
|                                   | PC stereo In                                   | 1   |                  |
| <b>Audio</b>                      | Built-in Speakers                              | Yes /2W x 2   |                  |
|                                   | Gradual Volume Increase                        | Yes   |                  |
| <b>Transmitter</b>                | Remote Control                                 | Yes   |                  |
| <b>Special Features</b>           | 3D Comfilter                                   | Yes   |                  |
|                                   | Deinterlace Function                           | Yes   |                  |
|                                   | Video Resolution(Max)                          | 520 TV line   |                  |
|                                   | LCD Protection Glass                           | Yes   |                  |
|                                   | Rack Mountable Kit                             | Not Available   |                  |
|                                   | Camera Mounting Hole                           | Not Available   |                  |
|                                   | OSD Language                                   | English, French, Deutsch, Italian<br>Espanol, Portugues , Nederland |                  |
|                                   | VESA™ Standard Compatible                      | Yes (Option)<br>100x100mm (BS M4x10mm Screw)                        |                  |
|                                   | <b>Additional Information</b>                  | Cabinet Dimensions (WxHxD)  | 430x428x200mm    |
|                                   |  | Weight  | 6.61Kg (14.6lbs) |
| Dimensions with Packaging (WxHxD) |  | 490 x 506 x 225 mm  |                  |
| Weight                            |  | 8.43Kg (18.6lbs)  |                  |
| Power Consumption                 |  | 50W   |                  |
| Power Source                      |  | DC 12V Adaptor<br>(AC100~240V(50/60Hz))                             |                  |
| <b>Cabinet</b>                    | Finish   | Black   |                  |
|                                   | Tilt Stand                                     | Yes   |                  |
| <b>Warranty</b>                   | Warranty: Parts/Labor                          |   |                  |
|                                   | MTBF (Approx.)                                 | 50K hrs.  |                  |
| <b>Regulations</b>                | UL(=same as TUV-NRTL), CB, FCC(B), CE-EMC(LVD) |   |                  |

### DIMENSIONS

Units : mm

